

LAW OFFICES

ROSENBERG, KLEIN & LEE

CHARTERED

MORTON J. ROSENBERG
DAVID I. KLEIN
JUN Y. LEE
HARRY L. SERNAKER

PATENT AGENTS
DAVID WOOD

3458 ELLICOTT CENTER DRIVE - SUITE 101

ELLICOTT CITY, MARYLAND 21043

PHONE (410)-465-6678 OR (410)-465-MORT

TELEFAX (410)-461-3067

INTERNET: rkl@rkllpatlaw.com

PATENT, TRADEMARK & COPYRIGHT MATTERS

PATENT RESEARCH
SPECIALISTS

JOHN V. PRESTIA
RAYMOND J. DUDEK
EVA BURDMAN
MORGAN D. ROSENBERG
PHILIP A. BENDER

FAX RECEIVED

JUL 31 2003

DATE: 31 July 2003TIME SENT: 11:05 AM TECHNOLOGY CENTER 28TOTAL PAGES (INCLUDING COVER SHEET): 8ATTENTION: EXAMINER Y. COMASCOMPANY NAME: U.S.P.T.O., ART UNIT #2834TO FAX NUMBER: (703) 872-9318

TRANSMITTING FROM: ROSENBERG, KLEIN & LEE

Facsimile Number: 410-461-3067

Telephone Number: 410-465-6678

OUR DOCKET NO. MR 1683-380 ~~YOUR REFERENCE~~ S/N 10/052,543PLEASE NOTIFY US AT ONCE IF NOT RECEIVED PROPERLY.

ADDITIONAL COMMENTS:

AMENDMENT FOR ENTRY

MR1683-380

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Chio Sung Chang

Serial No: 10/052,543

Group Art Unit: 2834

Filing Date: 01/23/2002

Examiner: COMAS, YAHVEH

For: MAGNETIC MATERIAL FIXING STRUCTURE OF MOTOR

ROTOR

Honorable Commissioner for Patents

P.O. Box 1450

Alexandria, VA 22313-1450

FAX RECEIVED

JUL 31 2003

TECHNOLOGY CENTER 2800

Sir,

Responsive to the Office Action mailed on May 01, 2003, please amend the above-identified application as follows:

AMENDMENT**IN THE CLAIM**

Please cancel claim 2 without prejudice or disclaimer of the subject matter thereof, and replace original claim 1 with the clean copy of amended claim 1, as follows:

CLEAN COPY OF THE AMMENDED CLAIMS

1. (Amended) A magnetic material fixing structure of motor rotor, comprising at least one silicon steel plate, an outer circumference of the silicon steel plate being recessed to form multiple receptacles at equal intervals, a magnetic material being disposed in each receptacles, each receptacle and the silicon steel plate defining two lateral faces, a bottom face and an opening opposite to the bottom face, the opening of the receptacle being slightly smaller than an internal width of the receptacle and the two lateral faces being slopes gradually diverging from outer side